

Specifications

Starfoil Pro Line Victoria cylinder press

Print specifications

Speed	3000 IPH
Max. sheet size	730 x 1040 mm
Min. sheet size	290 x 400 mm
Foiling area, mm	720 x 1038 mm
Feeder pile height	500 mm
Delivery pile height	850 mm
Grip Distance	5 mm
Max. sheet thickness	0.65 mm

Machine specification

Length	5,4 m
Width (incl. preloader)	4,35 m
Height (feeder wheels up)	2,19 m (2,8 m)
Total power	30 kW, 380 V - 415 V, 3 phase plus neutral & earth
PLC control	Yes
Electronic speed control	Yes
Electronic pile lift	Yes
Touch screen controls	Translated according to customer's specification
Diagnostic modem	Yes

Foil specification

Max. foil diameter	125 mm (610 m) @ 12 microns
Min. distance between foil rolls	0.5 mm
Number of foil units	2 standard; 3 - 4 optional
Number of lengths per program	3, more optional
Number of pulls per length	99
Foil bar	2
Foil tray	1
Pull resolution	0.1 mm
Hologram registration system	Up to 4 with stepping facilities

Bed specification

Heated zones	6
Adjustable zones (optional)	6
Sensors per zone	1
Max. adjustment	1 mm
Max. temperature	220°C

Die height

6.35 mm or 7 mm
